

DATA SHEET

4SSH3P

PRODUCT DESCRIPTION

PRODUCT NAME: SILICONE COATED FIBERGLASS HOSE PIPE 3 PLY **COLOR:** BRICK RED
PRODUCT DESCRIPTION: The standard hose pipe for high temp. Air flow & fume removal. The internal ply provides a smoother bore for maximum air flow, less.

TECHNICAL SPECIFICATION:-

APPLICATIONS:-

DIAMETER (MM)	WORK PRESSURE (BAR*) ±5%	MAX VACUUM (MM/W.G*) ±5%	BENDING RADIUS (MM) ±5%	WEIGHT (GR/MT) ±5%
25	3.5	8165	10.2	231.3
38	3.25	6900	15.3	381.3
51	3.25	5980	20.4	450
63	3	5290	26.4	606.3
76	2.75	4945	32.3	725
89	2.5	4600	37.4	862.5
95	2.38	4255	41.7	912.5
102	2.38	4025	44.2	962.5
114	1.88	3450	51	1056
127	1.75	2760	58.7	1156.3
152	1.25	1955	63.8	1500
178	1.25	1380	76.5	1787.5
203	0.88	1035	85.9	2062.5
250	0.63	805	127.5	2612.5
305	0.38	575	170	3187.5
400	0.38	518	225	3500
510	0.28	415	280	4375

- Tiles And Ceramic Machinery (Roller Kiln)
- Air Dryer
- Hopper Dryer
- Computer Cooling
- Direct Heater
- Vehicle Exhaust
- Hot Air Conveying System And All Industrial & Hot and Low Temp.

TEMPERATURE RANGE: -75° TO 1200° F & ABOVE,
CONTINUOUS TEMP. 350°C

STANDARD SIZE: 5 MTR & CUSTOMIZED